

Goodness-of-fit measures to compare observed and simulated time series with hydroGOF

Mauricio Zambrano-Bigiarini*

version 0.3, 21-Jan-2024

1 Citation

If you use *hydroGOF*, please cite it as Zambrano-Bigiarini (2024):

Zambrano-Bigiarini, M. (2024) hydroGOF: Goodness-of-fit functions for comparison of simulated and observed hydrological time series R package version 0.5-4. URL: <https://cran.r-project.org/package=hydroGOF>. doi:10.5281/zenodo.839854.

2 Installation

Installing the latest stable version (from CRAN):

```
install.packages("hydroGOF")
```

Alternatively, you can also try the under-development version (from Github):

```
if (!require(devtools)) install.packages("devtools")
library(devtools)
install_github("hzambran/hydroGOF")
```

3 Setting up the environment

Loading the *hydroGOF* package, which contains data and functions used in this analysis:

```
library(hydroGOF)
```

```
## Loading required package: zoo
##
## Attaching package: 'zoo'
## The following objects are masked from 'package:base':
##
##   as.Date, as.Date.numeric
```

4 Example using NSE

The following examples use the well-known Nash-Sutcliffe efficiency (NSE), but you can repeat the computations using any of the goodness-of-fit measures included in the *hydroGOF* package (e.g., KGE, ubRMSE, dr).

*mauricio.zambrano@ufrontera.cl

4.1 Example 1

Basic ideal case with a numeric sequence of integers:

```
obs <- 1:10
sim <- 1:10
NSE(sim, obs)
```

```
## [1] 1
```

```
obs <- 1:10
sim <- 2:11
NSE(sim, obs)
```

```
## [1] 0.8787879
```

4.2 Example 2

From this example onwards, a streamflow time series will be used.

First, we load the daily streamflows of the Ega River (Spain), from 1961 to 1970:

```
data(EgaEnEstellaQts)
obs <- EgaEnEstellaQts
```

Generating a simulated daily time series, initially equal to the observed series:

```
sim <- obs
```

Computing the ‘NSE’ for the “best” (unattainable) case

```
NSE(sim=sim, obs=obs)
```

```
## [1] 1
```

4.3 Example 3


NSE for simulated values equal to observations plus random noise on the first half of the observed values.

This random noise has more relative importance for low flows than for medium and high flows.

Randomly changing the first 1826 elements of ‘sim’, by using a normal distribution with mean 10 and standard deviation equal to 1 (default of ‘rnorm’).

```
sim[1:1826] <- obs[1:1826] + rnorm(1826, mean=10)
ggof(sim, obs)
```

Observations vs Simulations



GoF's:	
ME	= 5
MAE	= 5
RMSE	= 7.1
NRMSE	= 35.5
PBIAS	= 31.6
RSR	= 0.35
rSD	= 1.03
NSE	= 0.87
mNSE	= 0.61
rNSE	= -0.58
d	= 0.97
md	= 0.8
rd	= 0.62
r	= 0.97
R2	= 0.87
bR2	= 0.78
KGE	= 0.68
VE	= 0.68

```
NSE(sim=sim, obs=obs)
```

```
## [1] 0.8740285
```

Let's have a look at other goodness-of-fit measures:

```
mNSE(sim=sim, obs=obs) # modified NSE
```

```
## [1] 0.6050862
```

```
rNSE(sim=sim, obs=obs) # relative NSE
```

```
## [1] -0.579044
```

```
KGE(sim=sim, obs=obs) # Kling-Gupta efficiency (KGE), 2009
```

```
## [1] 0.6806871
```

```
KGE(sim=sim, obs=obs, method="2012") # Kling-Gupta efficiency (KGE), 2012
```

```
## [1] 0.617007
```

```
KGElf(sim=sim, obs=obs) # KGE for low flows
```

```
## [1] 0.5167163
```

```
KGEnp(sim=sim, obs=obs) # Non-parametric KGE
```

```
## [1] 0.6335115
```

```
sKGE(sim=sim, obs=obs) # Split KGE
```

```
## [1] 0.6545119
```

```
d(sim=sim, obs=obs) # Index of agreement (d)
```


```
## [1] 0.9697355
```

```

rd(sim=sim, obs=obs)           # Relative d
## [1] 0.6206367
md(sim=sim, obs=obs)           # Modified d
## [1] 0.7979001
dr(sim=sim, obs=obs)           # Refined d
## [1] 0.8025431
VE(sim=sim, obs=obs)           # Volumetric efficiency
## [1] 0.6839554
cp(sim=sim, obs=obs)           # Coefficient of persistence
## [1] 0.4685783
pbias(sim=sim, obs=obs)        # Percent bias (PBIAS)
## [1] 31.6
pbiasfdc(sim=sim, obs=obs)     # PBIAS in the slope of the midsegment of the FDC
## [Note: 'thr.shw' was set to FALSE to avoid confusing legends...]

```

Flow Duration Curve



```

## [1] -35.26538
rmse(sim=sim, obs=obs)         # Root mean square error (RMSE)
## [1] 7.102935
ubRMSE(sim=sim, obs=obs)       # Unbiased RMSE

```

```
## [1] 5.047561
rPearson(sim=sim, obs=obs)      # Pearson correlation coefficient

## [1] 0.9698054
rSpearman(sim=sim, obs=obs)     # Spearman rank correlation coefficient

## [1] 0.8351639
R2(sim=sim, obs=obs)           # Coefficient of determination (R2)

## [1] 0.8740285
br2(sim=sim, obs=obs)          # R2 multiplied by the slope of the regression line

## [1] 0.7781189
```

4.4 Example 4:

NSE for simulated values equal to observations plus random noise on the first half of the observed values and applying (natural) logarithm to 'sim' and 'obs' during computations.

```
NSE(sim=sim, obs=obs, fun=log)
```

```
## [1] 0.4782833
```

Verifying the previous value:

```
lsim <- log(sim)
lobs <- log(obs)
NSE(sim=lsim, obs=lobs)
```

```
## [1] 0.4782833
```

Let's have a look at other goodness-of-fit measures:

```
mNSE(sim=sim, obs=obs, fun=log)      # modified NSE
```

```
## [1] 0.4820242
```

```
rNSE(sim=sim, obs=obs, fun=log)     # relative NSE
```

```
## [1] -4.511849
```

```
KGE(sim=sim, obs=obs, fun=log)      # Kling-Gupta efficiency (KGE), 2009
```

```
## [1] 0.7152824
```

```
KGE(sim=sim, obs=obs, method="2012", fun=log) # Kling-Gupta efficiency (KGE), 2012
```

```
## [1] 0.6347871
```

```
KGElf(sim=sim, obs=obs)             # KGE for low flows (it does not allow 'fun' argument)
```

```
## [1] 0.5167163
```

```
KGEnp(sim=sim, obs=obs, fun=log)    # Non-parametric KGE
```

```
## [1] 0.7429642
```

```
sKGE(sim=sim, obs=obs, fun=log)     # Split KGE
```


```
## [1] 0.4646545
```

```

d(sim=sim, obs=obs, fun=log)           # Index of agreement (d)
## [1] 0.8605668
rd(sim=sim, obs=obs, fun=log)         # Relative d
## [1] -0.4730878
md(sim=sim, obs=obs, fun=log)         # Modified d
## [1] 0.7384767
dr(sim=sim, obs=obs, fun=log)         # Refined d
## [1] 0.7410121
VE(sim=sim, obs=obs, fun=log)         # Volumetric efficiency
## [1] 0.812349
cp(sim=sim, obs=obs, fun=log)         # Coefficient of persistence
## [1] -7.976549
pbias(sim=sim, obs=obs, fun=log)       # Percent bias (PBIAS)
## [1] 18.8
pbiasfdc(sim=sim, obs=obs, fun=log)    # PBIAS in the slope of the midsegment of the FDC
## [Note: 'thr.shw' was set to FALSE to avoid confusing legends...]

```

Flow Duration Curve



```

## [1] -46.72559
rmse(sim=sim, obs=obs, fun=log)       # Root mean square error (RMSE)

```

```
## [1] 0.6966453
ubRMSE(sim=sim, obs=obs, fun=log)           # Unbiased RMSE

## [1] 0.553272
rPearson(sim=sim, obs=obs, fun=log)         # Pearson correlation coefficient (r)

## [1] 0.821343
rSpearman(sim=sim, obs=obs, fun=log)        # Spearman rank correlation coefficient (rho)

## [1] 0.8351639
R2(sim=sim, obs=obs, fun=log)               # Coefficient of determination (R2)

## [1] 0.4782833
br2(sim=sim, obs=obs, fun=log)              # R2 multiplied by the slope of the regression line

## [1] 0.4285461
```

4.5 Example 5

NSE for simulated values equal to observations plus random noise on the first half of the observed values and applying (natural) logarithm to 'sim' and 'obs' and adding the Pushpalatha2012 constant during computations

```
NSE(sim=sim, obs=obs, fun=log, epsilon.type="Pushpalatha2012")
```

```
## [1] 0.4854824
```

Verifying the previous value, with the epsilon value following Pushpalatha2012:

```
eps  <- mean(obs, na.rm=TRUE)/100
lsim <- log(sim+eps)
lobs <- log(obs+eps)
NSE(sim=lsim, obs=lobs)
```

```
## [1] 0.4854824
```

Let's have a look at other goodness-of-fit measures:

```
gof(sim=sim, obs=obs, fun=log, epsilon.type="Pushpalatha2012", do.spearman=TRUE, do.pbfdc=TRUE)
```

```
##           [,1]
## ME         0.41
## MAE        0.41
## MSE        0.46
## RMSE       0.68
## ubRMSE     0.54
## NRMSE %    71.70
## PBIAS %    18.20
## RSR        0.72
## rSD        0.89
## NSE        0.49
## mNSE       0.48
## rNSE       -2.07
## wNSE       0.74
## wsNSE      0.78
## d          0.86
## dr         0.74
```

```
## md          0.74
## rd          0.18
## cp         -7.71
## r           0.83
## R2          0.49
## bR2        0.44
## VE         0.82
## KGE        0.72
## KGElf      0.52
## KGEmp      0.74
## KGEkm      0.74
## sKGE       0.53
## APFB       0.01
## HFB        0.01
## rSpearman  0.84
## pbiasFDC % -46.21
```

4.6 Example 6

NSE for simulated values equal to observations plus random noise on the first half of the observed values and applying (natural) logarithm to 'sim' and 'obs' and adding a user-defined constant during computations

```
eps <- 0.01
NSE(sim=sim, obs=obs, fun=log, epsilon.type="otherValue", epsilon.value=eps)
```

```
## [1] 0.4787542
```

Verifying the previous value:

```
lsim <- log(sim+eps)
lobs <- log(obs+eps)
NSE(sim=lsim, obs=lobs)
```

```
## [1] 0.4787542
```

Let's have a look at other goodness-of-fit measures:

```
gof(sim=sim, obs=obs, fun=log, epsilon.type="otherValue", epsilon.value=eps, do.spearman=TRUE, do.pbfdc=
```

```
##           [,1]
## ME        0.42
## MAE       0.42
## MSE       0.48
## RMSE      0.70
## ubRMSE    0.55
## NRMSE %   72.20
## PBIAS %   18.70
## RSR       0.72
## rSD       0.88
## NSE       0.48
## mNSE      0.48
## rNSE      -4.17
## wNSE      0.74
## wsNSE     0.78
## d         0.86
## dr        0.74
## md        0.74
```



```
## rd          -0.38
## cp          -7.96
## r           0.82
## R2          0.48
## bR2        0.43
## VE         0.81
## KGE         0.72
## KGElf      0.51
## KGEnp      0.74
## KGEkm      0.74
## sKGE       0.48
## APFB       0.01
## HFB        0.01
## rSpearman  0.84
## pbiasFDC % -46.69
```

4.7 Example 7

NSE for simulated values equal to observations plus random noise on the first half of the observed values and applying (natural) logarithm to 'sim' and 'obs' and using a user-defined factor to multiply the mean of the observed values to obtain the constant to be added to 'sim' and 'obs' during computations

```
fact <- 1/50
NSE(sim=sim, obs=obs, fun=log, epsilon.type="otherFactor", epsilon.value=fact)
```

```
## [1] 0.4922064
```

Verifying the previous value:

```
fact <- 1/50
eps <- fact*mean(obs, na.rm=TRUE)
lsim <- log(sim+eps)
lobs <- log(obs+eps)
NSE(sim=lsim, obs=lobs)
```

```
## [1] 0.4922064
```

Let's have a look at other goodness-of-fit measures:

```
gof(sim=sim, obs=obs, fun=log, epsilon.type="otherFactor", epsilon.value=fact, do.spearman=TRUE, do.pbf=TRUE)
```

```
##           [,1]
## ME         0.41
## MAE        0.41
## MSE        0.44
## RMSE       0.66
## ubRMSE     0.52
## NRMSE %    71.20
## PBIAS %    17.60
## RSR        0.71
## rSD        0.89
## NSE        0.49
## mNSE       0.48
## rNSE       -1.33
## wNSE       0.74
## wsNSE      0.78
## d          0.87
```

```
## dr          0.74
## md          0.74
## rd          0.38
## cp         -7.46
## r           0.83
## R2          0.49
## bR2         0.44
## VE          0.82
## KGE         0.73
## KGE1f       0.53
## KGEmp       0.74
## KGEkm       0.75
## sKGE        0.56
## APFB        0.01
## HFB         0.01
## rSpearman   0.84
## pbiasFDC % -45.71
```

4.8 Example 8

NSE for simulated values equal to observations plus random noise on the first half of the observed values and applying a user-defined function to 'sim' and 'obs' during computations:

```
fun1 <- function(x) {sqrt(x+1)}
NSE(sim=sim, obs=obs, fun=fun1)
```

```
## [1] 0.7259384
```

Verifying the previous value, with the epsilon value following Pushpalatha2012:

```
sim1 <- sqrt(sim+1)
obs1 <- sqrt(obs+1)
NSE(sim=sim1, obs=obs1)
```

```
## [1] 0.7259384
```

```
gof(sim=sim, obs=obs, fun=fun1, do.spearman=TRUE, do.pbfdc=TRUE)
```

```
##           [,1]
## ME         0.65
## MAE        0.65
## MSE        0.92
## RMSE       0.96
## ubRMSE     0.71
## NRMSE %    52.30
## PBIAS %    17.70
## RSR        0.52
## rSD        0.97
## NSE        0.73
## mNSE       0.54
## rNSE       0.34
## wNSE       0.89
## wsNSE      0.76
## d          0.93
## dr         0.77
## md         0.76
## rd         0.83
```

```
## cp          -1.17
## r           0.92
## R2          0.73
## bR2        0.65
## VE         0.82
## KGE        0.81
## KGElf      0.50
## KGEmp      0.75
## KGEkm      0.80
## sKGE       0.84
## APFB       0.02
## HFB        0.03
## rSpearman  0.84
## pbiasFDC % -33.26
```

5 A short example from hydrological modelling

Loading observed streamflows of the Ega River (Spain), with daily data from 1961-Jan-01 up to 1970-Dec-31

```
require(zoo)
data(EgaEnEstellaQts)
obs <- EgaEnEstellaQts
```

Generating a simulated daily time series, initially equal to the observed values (simulated values are usually read from the output files of the hydrological model)

```
sim <- obs
```

Computing the numeric goodness-of-fit measures for the “best” (unattainable) case

```
gof(sim=sim, obs=obs)
```

```
##          [,1]
## ME          0
## MAE         0
## MSE         0
## RMSE        0
## ubRMSE      0
## NRMSE %     0
## PBIAS %     0
## RSR         0
## rSD         1
## NSE         1
## mNSE        1
## rNSE        1
## wNSE        1
## wsNSE       1
## d           1
## dr          1
## md          1
## rd          1
## cp          1
## r           1
## R2          1
## bR2         1
## VE          1
```


```
## KGE      1
## KGElf   1
## KGEnp   1
## KGEkm   1
## sKGE    1
## APFB    0
## HFB     0
```

- Randomly changing the first 1826 elements of 'sim' (half of the ts), by using a normal distribution with mean 10 and standard deviation equal to 1 (default of 'rnorm').

```
sim[1:1826] <- obs[1:1826] + rnorm(1826, mean=10)
```

Plotting the graphical comparison of 'obs' against 'sim', along with the numeric goodness-of-fit measures for the daily and monthly time series


```
ggof(sim=sim, obs=obs, ftype="dm", FUN=mean)
```




5.1 Removing warm-up period

Using the first two years (1961-1962) as warm-up period, and removing the corresponding observed and simulated values from the computation of the goodness-of-fit measures:

```
gof(sim=sim, obs=obs, ftype="dm", FUN=mean, cal.ini="1963-01-01")
```



GoFs:	
ME	= 3.77
MAE	= 3.77
RMSE	= 6.19
NRMSE	= 33.9
PBIAS	= 25.3
RSR	= 0.34
rSD	= 1.02
NSE	= 0.88
mNSE	= 0.68
rNSE	= -0.5
d	= 0.97
md	= 0.84
rd	= 0.63
r	= 0.96
R2	= 0.88
bR2	= 0.81
KGE	= 0.74
VE	= 0.75



GoFs:	
ME	= 3.77
MAE	= 3.77
RMSE	= 6.16
NRMSE	= 46.1
PBIAS	= 25.3
RSR	= 0.46
rSD	= 1.04
NSE	= 0.79
mNSE	= 0.65
rNSE	= -1.46
d	= 0.95
md	= 0.82
rd	= 0.41
r	= 0.94
R2	= 0.79
bR2	= 0.7
KGE	= 0.74
VE	= 0.75

Verification of the goodness-of-fit measures for the daily values after removing the warm-up period:

```
sim <- window(sim, start="1963-01-01")
obs <- window(obs, start="1963-01-01")

gof(sim, obs)
```

```
##      [,1]
## ME    3.77
## MAE    3.77
## MSE   38.26
## RMSE    6.19
## ubRMSE  4.90
## NRMSE % 33.90
## PBIAS % 25.30
## RSR     0.34
## rSD     1.02
## NSE     0.88
## mNSE    0.68
## rNSE   -0.50
## wNSE    0.98
## wsNSE   0.82
## d       0.97
## dr      0.84
## md      0.84
```


```
## rd      0.63
## cp      0.51
## r       0.96
## R2      0.88
## bR2     0.81
## VE      0.75
## KGE     0.74
## KGE1f   0.57
## KGEmp   0.69
## KGEkm   0.74
## sKGE    0.70
## APFB    0.03
## HFB     0.00
```

5.2 Plotting uncertainty bands

Generating fictitious lower and upper uncertainty bounds:

```
lband <- obs - 5
uband <- obs + 5
plotbands(obs, lband, uband)
```


Confidence Bounds for 'x'



Plotting the previously generated uncertainty bands:

```
plotbands(obs, lband, uband)
```

Confidence Bounds for 'x'




Randomly generating a simulated time series:

```
sim <- obs + rnorm(length(obs), mean=3)
```

Plotting the previously generated simulated time series along the observations and the uncertainty bounds:

```
plotbands(obs, lband, uband, sim)
```

Confidence Bounds for 'x'



5.3 Analysis of the residuals

Computing the daily residuals (even if this is a dummy example, it is enough for illustrating the capability)

```
r <- sim-obs
```










Summarizing and plotting the residuals (it requires the hydroTSM package):

```
library(hydroTSM)
smry(r)
```

```
##           Index      r
## Min.      1963-01-01 -0.1221
## 1st Qu.   1964-12-31  2.3170
## Median    1966-12-31  2.9650
## Mean      1966-12-31  2.9930
## 3rd Qu.   1968-12-30  3.6720
## Max.      1970-12-31  6.7390
## IQR       <NA>      1.3549
## sd        <NA>      0.9895
## cv        <NA>      0.3306
## Skewness  <NA>      0.0512
## Kurtosis  <NA>     -0.0229
## NA's      <NA>      2.0000
## n         <NA>    2922.0000
```


```
# daily, monthly and annual plots, boxplots and histograms
```

```
hydroplot(r, FUN=mean)
```

Seasonal plots and boxplots

```
# daily, monthly and annual plots, boxplots and histograms
hydroplot(r, FUN=mean, pfreq="seasonal")
```



6 Software details

This tutorial was built under:

```
## [1] "x86_64-pc-linux-gnu"
## [1] "R version 4.4.1 Patched (2024-07-05 r86875)"
## [1] "hydroGOF 0.6-0.1"
```

7 Version history

- v0.3: Jan-2024
- v0.2: Mar-2020
- v0.1: Aug 2011