

Package ‘sasr’

May 24, 2023

Type Package

Title 'SAS' Interface

Version 0.1.2

Date 2023-04-26

Description Provides a 'SAS' interface, through 'SASPy'(<<https://sassoftware.github.io/saspy/>>) and 'reticulate'(<<https://rstudio.github.io/reticulate/>>).

This package helps you create 'SAS' sessions, execute 'SAS' code in remote 'SAS' servers, retrieve execution results and log, and exchange datasets between 'SAS' and 'R'.

It also helps you to install 'SASPy' and create a configuration file for the connection. Please review the 'SASPy' license file as instructed so that you comply with its separate and independent license.

License Apache License 2.0

URL <https://github.com/insightsengineering/sasr/>

BugReports <https://github.com/insightsengineering/sasr/issues>

Depends R (>= 3.6)

Imports checkmate, reticulate

Suggests knitr, mockery, testthat (>= 3.0.0)

VignetteBuilder knitr

biocViews

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.2.3

NeedsCompilation no

Author Liming Li [aut, cre],
Daniel Sabanes Bove [aut],
Isaac Gravestock [aut],
F. Hoffmann-La Roche AG [cph, fnd]

Maintainer Liming Li <liming.li@roche.com>

Repository CRAN

Date/Publication 2023-05-24 07:50:06 UTC

R topics documented:

sasr-package	2
df2sd	3
get_sas_cfg	3
get_sas_session	4
install_saspy	4
run_sas	5
sascfg	5
sas_session_ssh	7
sd2df	7
Index	8

sasr-package

sasr *Package*

Description

sasr provides interface to SAS through saspy and reticulate in R.

Author(s)

Maintainer: Liming Li <liming.li@roche.com>

Authors:

- Daniel Sabanes Bove <daniel.sabanes_bove@roche.com>
- Isaac Gravestock <isaac.gravestock@roche.com>

Other contributors:

- F. Hoffmann-La Roche AG [copyright holder, funder]

See Also

Useful links:

- <https://github.com/insightengineering/sasr/>
- Report bugs at <https://github.com/insightengineering/sasr/issues>

df2sd	<i>Transfer data.frame to SAS</i>
-------	-----------------------------------

Description

[Experimental] Transfer data.frame object from R environment to SAS.

Usage

```
df2sd(df, table = "_df", libref = "", ..., sas_session = get_sas_session())
```

Arguments

df	(data.frame) data frame to be transferred.
table	(character) table name in SAS.
libref	(character) library name in SAS.
...	additional arguments for saspy.sasbase.SASsession.df2sd
sas_session	(saspy.sasbase.SASsession) SAS session.

Value

"saspy.sasdata.SASdata" object.

get_sas_cfg	<i>Obtain the SAS Configuration File</i>
-------------	--

Description

[Experimental] Obtain the file path of the SAS configuration file.

Usage

```
get_sas_cfg()
```

Details

Obtain the default sas configuration file. By default, it will search the sascfg_personal.py file under current directory. If it does not exist, it will search this file under home directory. If this file does not exist, NULL will be returned.

Value

The file path of default SAS configuration file, or NULL if not found.

get_sas_session

Get the Last or Default SAS Session

Description

[Experimental] Obtain the last session or default session.

Usage

```
get_sas_session()
```

Details

this function is designed to facilitate the R users programming practice of function oriented programming instead of object oriented programmings.

Value

A new SAS session if there are no previous SAS session, or the last SAS session created.

install_saspy

Install saspy Module

Description

[Experimental] Install saspy module in reticulate.

Usage

```
install_saspy(method = "auto", conda = "auto")
```

Arguments

method	(character) method to install saspy.
conda	(character) path to conda executable.

Value

No return value.

run_sas	<i>Run SAS code with SAS Session</i>
---------	--------------------------------------

Description

[Experimental] Run SAS code with a SAS session.

Usage

```
run_sas(sas_code, results = c("TEXT", "HTML"), sas_session = get_sas_session())
```

Arguments

sas_code	(character) sas code to be executed.
results	(character) sas code execution results type.
sas_session	(saspy.sasbase.SASsession) SAS session.

Details

run_sas will run sas code through SAS session. The results is a named list of LST and LOG. The result part will be stored in LST, and log will be stored in LOG. If results argument is "TEXT", then results are in text format; if results argument is "HTML", then results are in html format.

Value

Named list with following elements:

- LOG: string of SAS execution log.
- LST: string of SAS execution result, in html or txt format.

sascfg	<i>Create SAS Session Configuration File</i>
--------	--

Description

[Experimental] Create SAS session configuration file based on argument.

Usage

```

sascfg(
  name = "default",
  host,
  saspath,
  ssh = system("which ssh", intern = TRUE),
  encoding = "latin1",
  options = list("-fullstimer"),
  ...,
  sascfg = "sascfg_personal.py"
)

```

Arguments

name	(character) name of the configuration.
host	(character) host name of remote server.
saspath	(character) SAS executable path on remote server.
ssh	(character) executable path of ssh.
encoding	(character) encoding of the SAS session.
options	(list) additional list of arguments to pass to ssh command.
...	additional arguments.
sascfg	(character) target file of configuration.

Details

host and saspath are required to connect to remote SAS server. Other arguments can follow default. If transferring datasets is needed, then tunnelling is required. Use tunnel = , rtunnel = to specify tunnels and reverse tunnels. The values should be length 1 integer.

Value

No return value.

sas_session_ssh	<i>Create SAS ssh Session Based on Configuration File</i>
-----------------	---

Description

[Experimental] Create a SAS ssh session.

Usage

```
sas_session_ssh(sascfg = get_sas_cfg())
```

Arguments

sascfg	(character) SAS session configuration.
--------	---

Value

SAS session.

sd2df	<i>Transfer SAS Data to R</i>
-------	-------------------------------

Description

[Experimental] Transfer the table in SAS session to R.

Usage

```
sd2df(table, libref = "", ..., sas_session = get_sas_session())
```

Arguments

table	(character) table name in SAS.
libref	(character) library name in SAS.
...	additional arguments for <code>saspy.sasbase.SASsession.sd2df</code>
sas_session	(<code>saspy.sasbase.SASsession</code>) SAS session.

Value

data.frame object.

Index

`_PACKAGE` (`sasr-package`), [2](#)

`df2sd`, [3](#)

`get_sas_cfg`, [3](#)

`get_sas_session`, [4](#)

`install_saspy`, [4](#)

`run_sas`, [5](#)

`sas_session_ssh`, [7](#)

`sascfg`, [5](#)

`sasr-package`, [2](#)

`sd2df`, [7](#)