

# BSgenome.Btaurus.UCSC.bosTau8

September 21, 2022

---

BSgenome.Btaurus.UCSC.bosTau8

*Full genome sequences for Bos taurus (UCSC version bosTau8)*

---

## Description

Full genome sequences for Bos taurus (Cow) as provided by UCSC (bosTau8, Jun. 2014) and stored in Biostrings objects.

## Note

This BSgenome data package was made from the following source data files:

bosTau8.2bit from <http://hgdownload.cse.ucsc.edu/goldenPath/bosTau8/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

## Author(s)

The Bioconductor Dev Team

## See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNASTring](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

**Examples**

```

BSgenome.Btaurus.UCSC.bosTau8
genome <- BSgenome.Btaurus.UCSC.bosTau8
head(seqlengths(genome))
genome$chr1 # same as genome[["chr1"]]

## -----
## Extract the upstream sequences
## -----
## The upstream sequences located in
## http://hgdownload.cse.ucsc.edu/goldenPath/bosTau8/bigZips/
## are based on RefSeq genes (RefSeq Genes track in the Genome Browser).
## These can easily be extracted from the full genome sequences with:

library(GenomicFeatures)
refGene_txdb <- suppressWarnings(makeTxDbFromUCSC("bosTau8", "refGene"))
refGene_up1000seqs <- extractUpstreamSeqs(genome, refGene_txdb)

## Note that you can make a TxDb object from various annotation
## resources. See the makeTxDbFromUCSC(), makeTxDbFromBiomart(), and
## makeTxDbFromGFF() functions in the GenomicFeatures package for more
## information.
## IMPORTANT: Make sure you use a TxDb package (or TxDb object) that
## contains a gene model based on bosTau8 or on a compatible genome
## (i.e. a genome with sequences identical to the sequences in bosTau8).
## See ?extractUpstreamSeqs in the GenomicFeatures package for more
## information.

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")

```

# Index

\* **data**

BSgenome.Btaurus.UCSC.bosTau8, [1](#)

\* **package**

BSgenome.Btaurus.UCSC.bosTau8, [1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Btaurus.UCSC.bosTau8, [1](#)

BSgenome.Btaurus.UCSC.bosTau8-package  
(BSgenome.Btaurus.UCSC.bosTau8),  
[1](#)

BSgenomeForge, [1](#)

Btaurus  
(BSgenome.Btaurus.UCSC.bosTau8),  
[1](#)

DNASTring, [1](#)