

# The pdfcolparcolumns package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2010/01/11 v1.3

## Abstract

Since version 1.40 pdfTeX supports several color stacks. This package uses them to fix color problems in package `parcolumns`.

## Contents

<b>1 Usage</b>	<b>2</b>
1.1 Option <code>rulebetweencolor</code>	2
1.2 Future	2
<b>2 Implementation</b>	<b>2</b>
2.1 Identification	2
2.2 Load packages	2
2.2.1 Package <code>parcolumns</code>	2
2.2.2 Package <code>pdfcol</code>	3
2.2.3 Package <code>infwarerr</code>	3
2.3 Color stack macros	3
2.4 Patches	3
2.4.1 Init stacks	3
2.4.2 Switch stack	3
2.4.3 Set current stack color	4
<b>3 Test</b>	<b>6</b>
<b>4 Installation</b>	<b>7</b>
4.1 Download	7
4.2 Bundle installation	7
4.3 Package installation	7
4.4 Refresh file name databases	7
4.5 Some details for the interested	8
<b>5 Catalogue</b>	<b>8</b>
<b>6 References</b>	<b>9</b>
<b>7 History</b>	<b>9</b>
[2007/07/26 v1.0]	9
[2007/09/09 v1.1]	9
[2008/08/11 v1.2]	9
[2010/01/11 v1.3]	9
<b>8 Index</b>	<b>9</b>

# 1 Usage

```
\usepackage{pdfcolparcolumns}
```

The package `pdfcolparcolumns` loads package `parcolumns` [1]. If color stacks are available then the macros of `parcolumns` are patched to add support for color stacks.

## 1.1 Option `rulebetweencolor`

Package `pdfcolparcolumns` also fixes the color for the rule between columns (if `rulebetween` is set). Default color is `\normalcolor`. But this can be changed by using option `rulebetweencolor`. It takes a color specification as value. If the value is empty, then the default (`\normalcolor`) is used. Examples:

```
rulebetweencolor=blue,  
rulebetweencolor={red},  
rulebetweencolor={}, % \normalcolor is used  
rulebetweencolor=[rgb]{1,0,.5} % see below
```

If used inside the optional argument of environment `parcolumns` and the value contains an optional argument, then whole value must be put in curly braces:

```
\begin{parcolumns}[  
  rulebetween,  
  rulebetweencolor={ [rgb]{1,0,.5} },  
]{2}  
  ...  
\end{parcolumns}
```

This option `rulebetweencolor` can also be set using `\setkeys`:

```
\setkeys{parcolumns}{rulebetweencolor=green}
```

## 1.2 Future

Currently package `parcolumns` does not seem to be maintained. Nevertheless if there will be a new version that adds support for color stacks, then this package may become obsolete.

# 2 Implementation

## 2.1 Identification

```
1 (*package)  
2 \NeedsTeXFormat{LaTeX2e}  
3 \ProvidesPackage{pdfcolparcolumns}%  
4 [2010/01/11 v1.3 Color stacks for parcolumns (HO)]%
```

## 2.2 Load packages

### 2.2.1 Package `parcolumns`

Currently package `parcolumns` does not define options. Thus it is just a precaution that the options of package `pdfcolparcolumns` are passed to package `parcolumns`.

```
5 \DeclareOption*{%  
6   \PassoptionsToPackage{\CurrentOption}{parcolumns}%  
7 }  
8 \ProcessOptions\relax  
9 \RequirePackage{parcolumns}[2004/11/25]
```

## 2.2.2 Package pdfcol

```
10 \RequirePackage{pdfcol}[2007/09/09]
11 \ifpdfcolAvailable
12 \else
13   \PackageInfo{pdfcolparcolumns}{%
14     Loading aborted, because color stacks are not available%
15   }%
16   \expandafter\endinput
17 \fi
```

## 2.2.3 Package infwarerr

```
18 \RequirePackage{infwarerr}[2007/09/09]
```

## 2.3 Color stack macros

`\pcpc@MaxStack` Macro `\pcpc@MaxStack` holds the highest number of allocated stacks.

```
19 \global\chardef\pcpc@MaxStack=\z@
```

`\pcpc@InitStacks` Macro `\pcpc@InitStacks` takes the number of columns as argument and ensures that there are enough color stacks for all columns.

```
20 \def\pcpc@InitStacks#1{%
21   \ifnum#1>\pcpc@MaxStack
22     \begingroup
23       \count@\pcpc@MaxStack
24       \loop
25         \advance\count@\@ne
26         \pdfcolInitStack{pcpc@\the\count@}%
27       \ifnum#1>\count@
28         \repeat
29       \global\chardef\pcpc@MaxStack=\count@
30     \endgroup
31   \fi
32 }
```

`\pcpc@SwitchStack`

```
33 \def\pcpc@SwitchStack#1{%
34   \pdfcolSwitchStack{pcpc@\number#1}%
35 }
```

`\pcpc@SetCurrent`

```
36 \def\pcpc@SetCurrent#1{%
37   \pdfcolSetCurrent{pcpc@\number#1}%
38 }
```

## 2.4 Patches

Now the color stack macros are patched into the macros of package `parcolumns`.

### 2.4.1 Init stacks

`\pcpc@InitStacks` should go into the definition of environment `parcolumns`. `\pc@alloccolumns` is executed there and nowhere else, thus we hook into it.

```
39 \g@addto@macro\pc@alloccolumns{%
40   \pcpc@InitStacks\pc@columncount
41 }
```

### 2.4.2 Switch stack

`\pcpc@SwitchStack` should be called by macro `\colchunk@`. However it is easier to patch `\pc@setcolumnwidth` that is executed in `\colchunk@` only.

```
42 \g@addto@macro\pc@setcolumnwidth{%
```

```

43 \pcpc@SwitchStack\pc@columnctr
44 }

```

### 2.4.3 Set current stack color

\pcpc@SetCurrent is set at the begin of each line. It must be inserted into \pc@placeboxes. Unhappily there is no easy way. Therefore we check and redefine \pc@placeboxes.

```

45 \beginngroup
46 \def\x{%
47 \global\let\@tempa\relax
48 \count@\z@
49 \hb@xt@\linewidth{%
50 \vfuzz30ex %
51 \vbadness\@M
52 \splittopskip\z@skip
53 \loop
54 \ifnum\count@<\pc@columncount
55 \advance\count@\@ne
56 \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
57 \hskip\csname pc@column@width@\number\count@\endcsname
58 \else
59 \expandafter\setbox\expandafter\@tempboxa\expandafter
60 \vsplit\csname pc@column@\number\count@\endcsname
61 to \dp\strutbox
62 \vbox{%
63 \unvbox\@tempboxa
64 }%
65 \fi
66 \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
67 \else
68 \global\let\@tempa\pc@placeboxes
69 \fi
70 \ifnum\count@<\pc@columncount
71 \strut
72 \hfill
73 \ifpc@rulebetween
74 \vrule
75 \hfill
76 \fi
77 \fi
78 \repeat
79 }%
80 \@tempa
81 }%
82 \ifx\x\pc@placeboxes
83 \else
84 \@PackageWarningNoLine{pdfcolparcolumns}{%
85 Command \string\pc@placeboxes\space has changed.\MessageBreak
86 Supported versions of package `parcolumns':\MessageBreak
87 \space\space 2004/08/05.\MessageBreak
88 The redefinition of \string\pc@placeboxes\space may not%
89 \MessageBreak
90 behave correctly depending on the changes%
91 }%
92 \fi
93 \endgroup

\pc@placeboxes

94 \renewcommand*\pc@placeboxes{%
95 \global\let\@tempa\relax
96 \count@\z@

```

```

97 \hb@xt@\linewidth{%
98 \vfuzz30ex %
99 \vbadness\@M
100 \splittopskip\z@skip
101 \loop
102 \ifnum\count@<\pc@columncount
103 \advance\count@\@ne
104 \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
105 \hskip\csname pc@column@width@\number\count@\endcsname
106 \else
107 \expandafter\setbox\expandafter\@tempboxa\expandafter
108 \vsplit\csname pc@column@\number\count@\endcsname
109 to \dp\strutbox
110 \vbox{%
111 \pcpc@SetCurrent\count@
112 \unvbox\@tempboxa
113 }%
114 \fi
115 \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
116 \else
117 \global\let\@tempa\pc@placeboxes
118 \fi
119 \ifnum\count@<\pc@columncount
120 \strut
121 \hfill
122 \ifpc@rulebetween
123 \begingroup
124 \pcpc@RuleBetweenColor
125 \vrule
126 \endgroup
127 \hfill
128 \fi
129 \fi
130 \repeat
131 }%
132 \@tempa
133 }

```

\pcpc@RuleBetweenColorDefault

```

134 \def\pcpc@RuleBetweenColorDefault{%
135 \normalcolor
136 }

```

\pcpc@RuleBetweenColor

```

137 \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault
138 \define@key{parcolumns}{rulebetweencolor}{%
139 \edef\pcpc@temp{#1}%
140 \ifx\pcpc@temp\@empty
141 \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault
142 \else
143 \edef\pcpc@temp{%
144 \noexpand\@ifnextchar [%
145 \def\noexpand\pcpc@RuleBetweenColor{%
146 \noexpand\color\pcpc@temp
147 }%
148 \noexpand\pcpc@GobbleNil
149 }{%
150 \def\noexpand\pcpc@RuleBetweenColor{%
151 \noexpand\color{\pcpc@temp}%
152 }%
153 \noexpand\pcpc@GobbleNil
154 }%

```

```

155     \pcpc@temp\noexpand\@nil
156   }%
157   \pcpc@temp
158   \fi
159 }

```

\pcpc@GobbleNil

```

160 \long\def\pcpc@GobbleNil#1\@nil{}
161 </package>

```

### 3 Test

The test file is a modified version of the file that Donald Goodman has posted in [comp.text.tex: "Re: xcolor glitches"](#)<sup>1</sup>

```

162 <*test1>
163 \NeedsTeXFormat{LaTeX2e}
164 \AtEndDocument{%
165   \typeout{%
166     \typeout{*****}%
167     \typeout{*** \space Check the PDF file manually! \space ***}%
168     \typeout{*****}%
169     \typeout{%
170   }
171 \documentclass{article}
172 \usepackage{xcolor}
173 \usepackage{pdfcolparcolumns}
174
175 \newcommand{\instruct}[1]{%
176   \noindent
177   \footnotesize
178   \textcolor{red}{#1}%
179 }
180
181 \begin{document}
182   \begin{parcolumns}[colwidths={1=2.3in,2=2.3in},sloppy]{2}%
183     \colchunk[1]{%
184       \instruct{Et non dicitur versus} %
185       Fidelium anim\ae\ %
186       \instruct{%
187         sed immediate subiungitur antiphona finalis %
188         beat\ae\ Mari\ae\ Virginis%
189       } %
190       100.%
191     }%
192     \colchunk[2]{%
193       \instruct{%
194         And the verse %
195         \textcolor{black}{May the souls of the faithful} %
196         is not said, but the final antiphon of the %
197         Blessed Virgin Mary, %
198         \textcolor{black}{100,} %
199         is immediately joined.%
200       }%
201     }%
202   \end{parcolumns}%
203 \end{document}
204 </test1>

```

<sup>1</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/8eda74ed292012bb>

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>2</sup>:

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\TeX$ :

```
tex pdfcolparcolumns.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcolparcolumns.sty      → tex/latex/oberdiek/pdfcolparcolumns.sty
pdfcolparcolumns.pdf     → doc/latex/oberdiek/pdfcolparcolumns.pdf
test/pdfcolparcolumns-test1.tex → doc/latex/oberdiek/test/pdfcolparcolumns-test1.tex
pdfcolparcolumns.dtx     → source/latex/oberdiek/pdfcolparcolumns.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 4.4 Refresh file name databases

If your  $\TeX$  distribution (te $\TeX$ , mik $\TeX$ , ...) relies on file name databases, you must refresh these. For example, te $\TeX$  users run `texhash` or `mktexlsr`.

---

<sup>2</sup><ftp://ftp.ctan.org/tex-archive/>

## 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcolparcolumns.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcolparcolumns.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
```

## 5 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcolparcolumns.xml`.

```
205 <?xml version='1.0' encoding='us-ascii'?>
206 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
207 <entry datestamp='$Date$' modifier='$Author$' id='pdfcolparcolumns'>
208   <name>pdfcolparcolumns</name>
209   <caption>Fix colour problems in package 'parcolumns'.</caption>
210   <authorref id='auth:oberdiek' />
211   <copyright owner='Heiko Oberdiek' year='2007,2008,2010' />
212   <license type='lppl1.3' />
213   <version number='1.3' />
214   <description>
215     Since version 1.40 pdfTeX supports colour stacks.
216     This package uses them to fix colour problems in
217     package <xref refid='parcolumns'>parcolumns</xref>.
218     <p />
219     The package is part of the <xref refid='oberdiek'>oberdiek</xref>
220     bundle.
221   </description>
222   <documentation details='Package documentation'
223     href='ctan:/macros/latex/contrib/oberdiek/pdfcolparcolumns.pdf' />
224   <ctan file='true' path='/macros/latex/contrib/oberdiek/pdfcolparcolumns.dtx' />
225
```



```

226 <miktex location='oberdiek' />
227 <texlive location='oberdiek' />
228 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
229 </entry>
230 </catalogue>

```

## 6 References

- [1] Jonathan Sauer: *The parcolumns package*; 2004/11/25;  
[CTAN:macros/latex/contrib/sauerj/parcolumns.pdf](#).
- [2] Heiko Oberdiek: *The pdfcol package*; 2007/09/09;  
[CTAN:macros/latex/contrib/oberdiek/pdfcol.pdf](#).

## 7 History

### [2007/07/26 v1.0]

- First version, published in the newsgroup `comp.text.tex` with the name `parcolumns-colorstacks`: “[Re: xcolor glitches](#)”<sup>3</sup>

### [2007/09/09 v1.1]

- CTAN version, package name renamed to `pdfcolparcolumns`.
- Uses package `pdfcol`.
- Documentation added.
- Test file added.

### [2008/08/11 v1.2]

- Code is not changed.
- URLs updated.

### [2010/01/11 v1.3]

- Fix for rule color.
- New option `rulebetweencolor` for environment `parcolumns`.

## 8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@M</code> .....	51, 99
<code>\@PackageWarningNoLine</code> .....	84
<code>\@empty</code> .....	140
<code>\@ifnextchar</code> .....	144
<code>\@ne</code> .....	25, 55, 103
<code>\@nil</code> .....	155, 160
<code>\@tempa</code> .....	47, 68, 80, 95, 117, 132
<code>\@tempboxa</code> .....	59, 63, 107, 112
<code>\_</code> .....	185, 188
<b>A</b>	
<code>\advance</code> .....	25, 55, 103
<code>\ae</code> .....	185, 188
<code>\AtEndDocument</code> .....	164
<b>B</b>	
<code>\begin</code> .....	181, 182

<sup>3</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/56bd897b11bca414>

<b>C</b>	
<code>\chardef</code> .....	19, 29
<code>\colchunk</code> .....	183, 192
<code>\color</code> .....	146, 151
<code>\count@</code> ..	23, 25, 26, 27, 29, 48, 54, 55, 56, 57, 60, 66, 70, 96, 102, 103, 104, 105, 108, 111, 115, 119
<code>\csname</code> ..	56, 57, 60, 66, 104, 105, 108, 115
<code>\CurrentOption</code> .....	6
<b>D</b>	
<code>\DeclareOption</code> .....	5
<code>\define@key</code> .....	138
<code>\documentclass</code> .....	171
<code>\dp</code> .....	61, 109
<b>E</b>	
<code>\end</code> .....	202, 203
<code>\endcsname</code> .....	56, 57, 60, 66, 104, 105, 108, 115
<code>\endinput</code> .....	16
<b>F</b>	
<code>\footnotesize</code> .....	177
<b>G</b>	
<code>\g@addto@macro</code> .....	39, 42
<b>H</b>	
<code>\hb@xt@</code> .....	49, 97
<code>\hfill</code> .....	72, 75, 121, 127
<code>\hskip</code> .....	57, 105
<b>I</b>	
<code>\ifnum</code> .....	21, 27, 54, 70, 102, 119
<code>\ifpc@rulebetween</code> .....	73, 122
<code>\ifpdfcolAvailable</code> .....	11
<code>\ifvoid</code> .....	56, 66, 104, 115
<code>\ifx</code> .....	82, 140
<code>\instruct</code> .....	175, 184, 186, 193
<b>L</b>	
<code>\linewidth</code> .....	49, 97
<code>\loop</code> .....	24, 53, 101
<b>M</b>	
<code>\MessageBreak</code> .....	85, 86, 87, 89
<b>N</b>	
<code>\NeedsTeXFormat</code> .....	2, 163
<code>\newcommand</code> .....	175
<code>\noindent</code> .....	176
<code>\normalcolor</code> .....	135
<code>\number</code> .....	34, 37, 56, 57, 60, 66, 104, 105, 108, 115
<b>P</b>	
<code>\PackageInfo</code> .....	13
<code>\PassoptionsToPackage</code> .....	6
<code>\pc@allococolumns</code> .....	39
<code>\pc@columncount</code> ..	40, 54, 70, 102, 119
<code>\pc@columnctr</code> .....	43
<code>\pc@placeboxes</code> .....	68, 82, 85, 88, 94
<code>\pc@setcolumnwidth</code> .....	42
<code>\pcpc@GobbleNil</code> .....	148, 153, 160
<code>\pcpc@InitStacks</code> .....	20, 40
<code>\pcpc@MaxStack</code> .....	19, 21, 23, 29
<code>\pcpc@RuleBetweenColor</code> .....	124, 137, 141, 145, 150
<code>\pcpc@RuleBetweenColorDefault</code> ..	134, 137, 141
<code>\pcpc@SetCurrent</code> .....	36, 111
<code>\pcpc@SwitchStack</code> .....	33, 43
<code>\pcpc@temp</code> .....	139, 140, 143, 146, 151, 155, 157
<code>\pdfcolInitStack</code> .....	26
<code>\pdfcolSetCurrent</code> .....	37
<code>\pdfcolSwitchStack</code> .....	34
<code>\ProcessOptions</code> .....	8
<code>\ProvidesPackage</code> .....	3
<b>R</b>	
<code>\renewcommand</code> .....	94
<code>\repeat</code> .....	28, 78, 130
<code>\RequirePackage</code> .....	9, 10, 18
<b>S</b>	
<code>\setbox</code> .....	59, 107
<code>\space</code> .....	85, 87, 88, 167
<code>\splittopskip</code> .....	52, 100
<code>\strut</code> .....	71, 120
<code>\strutbox</code> .....	61, 109
<b>T</b>	
<code>\textcolor</code> .....	178, 195, 198
<code>\the</code> .....	26
<code>\typeout</code> .....	165, 166, 167, 168, 169
<b>U</b>	
<code>\unvbox</code> .....	63, 112
<code>\usepackage</code> .....	172, 173
<b>V</b>	
<code>\vbadness</code> .....	51, 99
<code>\vbox</code> .....	62, 110
<code>\vfuzz</code> .....	50, 98
<code>\vrule</code> .....	74, 125
<code>\vsplit</code> .....	60, 108
<b>X</b>	
<code>\x</code> .....	46, 82
<b>Z</b>	
<code>\z@</code> .....	19, 48, 96
<code>\z@skip</code> .....	52, 100