

# Package ‘MPFE’

October 17, 2020

**Type** Package

**Title** Estimation of the amplicon methylation pattern distribution from bisulphite sequencing data

**Version** 1.24.1

**Date** 2014-11-28

**Author** Peijie Lin, Sylvain Foret, Conrad Burden

**biocViews** HighThroughputSequencingData, DNAMethylation, MethylSeq

**Maintainer** Conrad Burden <conrad.burden@anu.edu.au>

**Description** Estimate distribution of methylation patterns from a table of counts from a bisulphite sequencing experiment given a non-conversion rate and read error rate.

**License** GPL (>= 3)

**git\_url** <https://git.bioconductor.org/packages/MPFE>

**git\_branch** RELEASE\_3\_11

**git\_last\_commit** db08854

**git\_last\_commit\_date** 2020-10-09

**Date/Publication** 2020-10-16

## R topics documented:

MPFE-package . . . . .	1
estimatePatterns . . . . .	2
patternMap . . . . .	3
patternsExample . . . . .	4
plotPatterns . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

MPFE-package	<i>MPFE</i>
--------------	-------------

---

## Description

Estimate distribution of methylation patterns from a table of counts from a bisulphite sequencing experiment given a non-conversion rate and sequencing error rate.

## Details

Package: MPFE  
 Type: Package  
 License: GPL(>=3)

The main component of this package is the function `estimatePatterns`, which reads a table of read counts of bisulphite sequencing data for a given amplicon and generates a table and plot of the estimated distribution over methylation patterns.

### Author(s)

Peijie Lin, Sylvain Foret, Conrad Burden  
 Maintainer: conrad.burden@anu.edu.au

### Examples

```
data(patternsExample)
estimates <- estimatePatterns(patternsExample, epsilon=0.02, eta=0.01)
estimates
plotPatterns(estimates[[2]])
```

---

estimatePatterns	<i>Estimate distribution of methylation patterns</i>
------------------	--

---

### Description

Estimate distribution of methylation patterns from a table of counts from a bisulphite sequencing experiment given a non-conversion rate and a sequencing error rate.

### Usage

```
estimatePatterns(patternCounts,
                 epsilon=0,
                 eta=0,
                 column=NULL,
                 fast=TRUE,
                 steps=20000,
                 reltol=1e-12)
```

### Arguments

patternCounts	data frame with methylation patterns in first column and pattern counts in subsequent columns.
epsilon	non-conversion rate, a value between 0 and 1.
eta	error rate, either a vector of numbers between 0 and 1 of length equal to the number of CpG sites or a single value between 0 and 1 for a single error rate across all sites.
column	a vector that specifies the indices of the columns of 'patternCounts' to process. Its entries are integer values from 1 to the number of pattern counts columns in 'patternCounts'. If NULL, defaults to all columns.

fast	logical, if TRUE, fast version implemented (default).
steps	number of steps for the optimiser, passed to <code>constrOptim</code> . If NULL, defaults to 20000 steps.
reltol	relative tolerance for the optimiser, passed to <code>constrOptim</code> . If NULL, defaults to 1e-12.

**Value**

The function returns a list of data frames.

The data frames contain the following columns:

pattern	the list of input patterns (factor)
coverage	the number of reads for each pattern (integer)
observedDistribution	the observed frequencies of each pattern (numeric)
estimatedDistribution	the estimated frequencies (numeric)
spurious	indicates whether the patterns are real or spurious (logical)

**Author(s)**

Peijie Lin, Sylvain Foret, Conrad Burden

**Examples**

```
data(patternsExample)
estimatePatterns(patternsExample,
  epsilon=0.02,
  eta=0.01)
estimatePatterns(patternsExample,
  epsilon=0.01,
  eta=c(0.015, 0.01, 0.01, 0.01, 0.015),
  column=2)
```

---

patternMap

*Plot a representation of the patterns and their frequencies*

---

**Description**

Plot the observed distribution and the estimated distribution of the methylation patterns

**Usage**

```
patternMap(patterns,
  minFreq=0,
  maxFreq=1,
  noSpurious=TRUE,
  estimatedDistribution=TRUE,
  topDown=TRUE,
  allTicks=FALSE,
  methCol='black',
  unMethCol='white',
  ...)
```

**Arguments**

patterns	A data frame obtained from the output of the function <code>estimatePatterns</code> .
minFreq	Only plot patterns with at least minFreq frequency.
maxFreq	Only plot patterns with more maxFreq frequency or more.
noSpurious	Don't plot spurious patterns (only relevant if estimatedDistribution is FALSE).
estimatedDistribution	Use the frequencies from the estimated distribution. If FALSE, use the observed distribution.
topDown	Put the most abundant patterns at the top. If FALSE the most abundant patterns are at the bottom.
allTicks	Draw a tick under every position.
methCol	The colour for the methylated positions. Can be a single colour, a vector of colours (recycled), or a function (for instance from <code>colorRampPalette</code> ).
unMethCol	As methCol but for un-methylated positions.
...	Other arguments passed to <code>plot</code>

**Details**

This function draws a map of the different pattern and their frequencies based on the values returned by `estimatePatterns`.

**Author(s)**

Peijie Lin, Sylvain Foret, Conrad Burden

**Examples**

```
data(patternsExample)
estimates <- estimatePatterns(patternsExample,
                              epsilon=0.02,
                              eta=0.01)
patternMap(estimates[[1]])
```

---

patternsExample

*patternsExample*

---

**Description**

A data frame which contains a column of methylation patterns and two columns of counts. This data was obtained as described in Lyko, F., Forest, S., Kucharski, R., Wolf, S., Falckenhayn, C., and Maleszka, R. (2010). The honey bee epigenomes: differential methylation of brain DNA in queens and workers. *PLoS Biol*, 8(11), e1000506.

**Usage**

```
data(patternsExample)
```



# Index

- \* **amplicon**,
  - MPFE-package, 1
- \* **bisufite sequencing**,
  - MPFE-package, 1
- \* **bisulphite sequencing**,
  - MPFE-package, 1
- \* **methylation**
  - MPFE-package, 1
- \*
  - MPFE-package, 1
- colorRampPalette, 4
- constrOptim, 3
- estimatePatterns, 2, 2, 4, 5
- MPFE (MPFE-package), 1
- MPFE-package, 1
- patternMap, 3
- patternsExample, 4
- plot, 4
- plotPatterns, 5