

illuminaHumanv2.db

August 27, 2020

illuminaHumanv2ACCNUM *Map Manufacturer identifiers to Accession Numbers*

Description

illuminaHumanv2ACCNUM is an R object that contains mappings between a manufacturer's identifiers and manufacturers accessions.

Details

For chip packages such as this, the ACCNUM mapping comes directly from the manufacturer. This is different from other mappings which are mapped onto the probes via an Entrez Gene identifier.

Each manufacturer identifier maps to a vector containing a GenBank accession number.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

Examples

```
x <- illuminaHumanv2ACCNUM
# Get the probe identifiers that are mapped to an ACCNUM
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the ACCNUM for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

```
illuminaHumanv2ALIAS2PROBE
```

Map between Common Gene Symbol Identifiers and Manufacturer Identifiers

Description

illuminaHumanv2ALIAS is an R object that provides mappings between common gene symbol identifiers and manufacturer identifiers.

Details

Each gene symbol is mapped to a named vector of manufacturer identifiers. The name represents the gene symbol and the vector contains all manufacturer identifiers that are found for that symbol. An NA is reported for any gene symbol that cannot be mapped to any manufacturer identifiers.

This mapping includes ALL gene symbols including those which are already listed in the SYMBOL map. The SYMBOL map is meant to only list official gene symbols, while the ALIAS maps are meant to store all used symbols.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

Examples

```
# Convert the object to a list
xx <- as.list(illuminaHumanv2ALIAS2PROBE)
if(length(xx) > 0){
  # Get the probe identifiers for the first two aliases
  xx[1:2]
  # Get the first one
  xx[[1]]
}
```

```
illuminaHumanv2.db    Bioconductor annotation data package
```

Description

Welcome to the illuminaHumanv2.db annotation Package. The purpose of this package is to provide detailed information about the illuminaHumanv2 platform. This package is updated biannually.

You can learn what objects this package supports with the following command:

```
ls("package:illuminaHumanv2.db")
```

Each of these objects has their own manual page detailing where relevant data was obtained along with some examples of how to use it.

Examples

```
ls("package:illuminaHumanv2.db")
```

illuminaHumanv2CHR *Map Manufacturer IDs to Chromosomes*

Description

illuminaHumanv2CHR is an R object that provides mappings between a manufacturer identifier and the chromosome that contains the gene of interest.

Details

Each manufacturer identifier maps to a vector of chromosomes. Due to inconsistencies that may exist at the time the object was built, the vector may contain more than one chromosome (e.g., the identifier may map to more than one chromosome). If the chromosomal location is unknown, the vector will contain an NA.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

Examples

```
x <- illuminaHumanv2CHR
# Get the probe identifiers that are mapped to a chromosome
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the CHR for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2CHRENGTHS

A named vector for the length of each of the chromosomes

Description

illuminaHumanv2CHRENGTHS provides the length measured in base pairs for each of the chromosomes.

Details

This is a named vector with chromosome numbers as the names and the corresponding lengths for chromosomes as the values.

Total lengths of chromosomes were derived by calculating the number of base pairs on the sequence string for each chromosome.

Examples

```
tt <- illuminaHumanv2CHRENGTHS
# Length of chromosome 1
tt["1"]
```

illuminaHumanv2CHRLOC *Map Manufacturer IDs to Chromosomal Location*

Description

illuminaHumanv2CHRLOC is an R object that maps manufacturer identifiers to the starting position of the gene. The position of a gene is measured as the number of base pairs.

The CHRLOCEND mapping is the same as the CHRLOC mapping except that it specifies the ending base of a gene instead of the start.

Details

Each manufacturer identifier maps to a named vector of chromosomal locations, where the name indicates the chromosome. Due to inconsistencies that may exist at the time the object was built, these vectors may contain more than one chromosome and/or location. If the chromosomal location is unknown, the vector will contain an NA.

Chromosomal locations on both the sense and antisense strands are measured as the number of base pairs from the p (5' end of the sense strand) to q (3' end of the sense strand) arms. Chromosomal locations on the antisense strand have a leading "-" sign (e. g. -1234567).

Since some genes have multiple start sites, this field can map to multiple locations.

Mappings were based on data provided by: UCSC Genome Bioinformatics (Homo sapiens) <ftp://hgdownload.cse.ucsc.edu>
With a date stamp from the source of: 2010-Mar22

Examples

```
x <- illuminaHumanv2CHRLOC
# Get the probe identifiers that are mapped to chromosome locations
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the CHRLOC for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2ENSEMBL

Map Ensembl gene accession numbers with Entrez Gene identifiers

Description

illuminaHumanv2ENSEMBL is an R object that contains mappings between manufacturer identifiers and Ensembl gene accession numbers.

Details

This object is a simple mapping of manufacturer identifiers to Ensembl gene Accession Numbers.

Mappings were based on data provided by BOTH of these sources: <http://www.ensembl.org/biomart/martview/> <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA>

For most species, this mapping is a combination of manufacturer to ensembl IDs from BOTH NCBI and ensembl. Users who wish to only use mappings from NCBI are encouraged to see the ncbi2ensembl table in the appropriate organism package. Users who wish to only use mappings from ensembl are encouraged to see the ensembl2ncbi table which is also found in the appropriate organism packages. These mappings are based upon the ensembl table which is contains data from BOTH of these sources in an effort to maximize the chances that you will find a match.

For worms and flies however, this mapping is based only on sources from ensembl, as these organisms do not have ensembl to entrez gene mapping data at NCBI.

Examples

```
x <- illuminaHumanv2ENSEMBL
# Get the entrez gene IDs that are mapped to an Ensembl ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the Ensembl gene IDs for the first five genes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
#For the reverse map ENSEMBL2PROBE:
# Convert to a list
xx <- as.list(illuminaHumanv2ENSEMBL2PROBE)
if(length(xx) > 0){
  # Gets the entrez gene IDs for the first five Ensembl IDs
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2ENTREZID

Map between Manufacturer Identifiers and Entrez Gene

Description

illuminaHumanv2ENTREZID is an R object that provides mappings between manufacturer identifiers and Entrez Gene identifiers.

Details

Each manufacturer identifier is mapped to a vector of Entrez Gene identifiers. An NA is assigned to those manufacturer identifiers that can not be mapped to an Entrez Gene identifier at this time.

If a given manufacturer identifier can be mapped to different Entrez Gene identifiers from various sources, we attempt to select the common identifiers. If a consensus cannot be determined, we select the smallest identifier.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene>

Examples

```
x <- illuminaHumanv2ENTREZID
# Get the probe identifiers that are mapped to an ENTREZ Gene ID
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the ENTREZID for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2ENZYME *Maps between Manufacturer IDs and Enzyme Commission (EC) Numbers*

Description

illuminaHumanv2ENZYME is an R object that provides mappings between manufacturer identifiers and EC numbers. illuminaHumanv2ENZYME2PROBE is an R object that maps Enzyme Commission (EC) numbers to manufacturer identifiers.

Details

When the illuminaHumanv2ENZYME mapping is viewed as a list, each manufacturer identifier maps to a named vector containing the EC number that corresponds to the enzyme produced by that gene. The names correspond to the manufacturer identifiers. If this information is unknown, the vector will contain an NA.

For the illuminaHumanv2ENZYME2PROBE, each EC number maps to a named vector containing all of the manufacturer identifiers that correspond to the gene that produces that enzyme. The name of the vector corresponds to the EC number.

Enzyme Commission numbers are assigned by the Nomenclature Committee of the International Union of Biochemistry and Molecular Biology <http://www.chem.qmw.ac.uk/iubmb/enzyme/> to allow enzymes to be identified.

An Enzyme Commission number is of the format EC x.y.z.w, where x, y, z, and w are numeric numbers. In illuminaHumanv2ENZYME2PROBE, EC is dropped from the Enzyme Commission numbers.

Enzyme Commission numbers have corresponding names that describe the functions of enzymes in such a way that EC x is a more general description than EC x.y that in turn is a more general description than EC x.y.z. The top level EC numbers and names are listed below:

EC 1 oxidoreductases

EC 2 transferases

EC 3 hydrolases

EC 4 lyases

EC 5 isomerases

EC 6 ligases

The EC name for a given EC number can be viewed at <http://www.chem.qmul.ac.uk/iupac/jcbn/index.html#6>

Mappings between probe identifiers and enzyme identifiers were obtained using files provided by: KEGG GENOME <ftp://ftp.genome.jp/pub/kegg/genomes> With a date stamp from the source of: 2011-Mar15

References

<ftp://ftp.genome.ad.jp/pub/kegg/pathways>

Examples

```
x <- illuminaHumanv2ENZYME
# Get the probe identifiers that are mapped to an EC number
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the ENZYME for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

# Now convert illuminaHumanv2ENZYME2PROBE to a list to see inside
xx <- as.list(illuminaHumanv2ENZYME2PROBE)
if(length(xx) > 0){
  # Get the probe identifiers for the first five enzyme
  #commission numbers
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2GENENAME

Map between Manufacturer IDs and Genes

Description

illuminaHumanv2GENENAME is an R object that maps manufacturer identifiers to the corresponding gene name.

Details

Each manufacturer identifier maps to a named vector containing the gene name. The vector name corresponds to the manufacturer identifier. If the gene name is unknown, the vector will contain an NA.

Gene names currently include both the official (validated by a nomenclature committee) and preferred names (interim selected for display) for genes. Efforts are being made to differentiate the two by adding a name to the vector.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

Examples

```
x <- illuminaHumanv2GENENAME
# Get the probe identifiers that are mapped to a gene name
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the GENENAME for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2GO

Maps between manufacturer IDs and Gene Ontology (GO) IDs

Description

illuminaHumanv2GO is an R object that provides mappings between manufacturer identifiers and the GO identifiers that they are directly associated with. This mapping and its reverse mapping (illuminaHumanv2GO2PROBE) do NOT associate the child terms from the GO ontology with the gene. Only the directly evidenced terms are represented here.

illuminaHumanv2GO2ALLPROBES is an R object that provides mappings between a given GO identifier and all of the manufacturer identifiers annotated at that GO term OR TO ONE OF IT'S CHILD NODES in the GO ontology. Thus, this mapping is much larger and more inclusive than illuminaHumanv2GO2PROBE.

Details

If illuminaHumanv2GO is cast as a list, each manufacturer identifier is mapped to a list of lists. The names on the outer list are GO identifiers. Each inner list consists of three named elements: GOID, Ontology, and Evidence.

The GOID element matches the GO identifier named in the outer list and is included for convenience when processing the data using 'lapply'.

The Ontology element indicates which of the three Gene Ontology categories this identifier belongs to. The categories are biological process (BP), cellular component (CC), and molecular function (MF).

The Evidence element contains a code indicating what kind of evidence supports the association of the GO identifier to the manufacturer id. Some of the evidence codes in use include:

IMP: inferred from mutant phenotype
 IGI: inferred from genetic interaction
 IPI: inferred from physical interaction
 ISS: inferred from sequence similarity
 IDA: inferred from direct assay
 IEP: inferred from expression pattern
 IEA: inferred from electronic annotation
 TAS: traceable author statement
 NAS: non-traceable author statement
 ND: no biological data available
 IC: inferred by curator

A more complete listing of evidence codes can be found at:

<http://www.geneontology.org/GO.evidence.shtml>

If `illuminaHumanv2GO2ALLPROBES` or `illuminaHumanv2GO2PROBE` is cast as a list, each GO term maps to a named vector of manufacturer identifiers and evidence codes. A GO identifier may be mapped to the same manufacturer identifier more than once but the evidence code can be different. Mappings between Gene Ontology identifiers and Gene Ontology terms and other information are available in a separate data package named `GO`.

Whenever any of these mappings are cast as a `data.frame`, all the results will be output in an appropriate tabular form.

Mappings between manufacturer identifiers and GO information were obtained through their mappings to manufacturer identifiers. NAs are assigned to manufacturer identifiers that can not be mapped to any Gene Ontology information. Mappings between Gene Ontology identifiers and Gene Ontology terms and other information are available in a separate data package named `GO`.

All mappings were based on data provided by: Gene Ontology <ftp://ftp.geneontology.org/pub/go/godatabase/archive/latest/> With a date stamp from the source of: 20150314

References

<ftp://ftp.ncbi.nlm.nih.gov/gene/DATA/>

See Also

[illuminaHumanv2GO2ALLPROBES](#).

Examples

```
x <- illuminaHumanv2GO
# Get the manufacturer identifiers that are mapped to a GO ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Try the first one
  got <- xx[[1]]
  got[[1]][["GOID"]]
  got[[1]][["Ontology"]]
  got[[1]][["Evidence"]]
}
```

```

# For the reverse map:
# Convert to a list
xx <- as.list(illuminaHumanv2GO2PROBE)
if(length(xx) > 0){
  # Gets the manufacturer ids for the top 2nd and 3rd GO identifiers
  goids <- xx[2:3]
  # Gets the manufacturer ids for the first element of goids
  goids[[1]]
  # Evidence code for the mappings
  names(goids[[1]])
}
# Convert illuminaHumanv2GO2ALLPROBES to a list
xx <- as.list(illuminaHumanv2GO2ALLPROBES)
if(length(xx) > 0){
  # Gets the manufacturer identifiers for the top 2nd and 3rd GO identifiers
  goids <- xx[2:3]
  # Gets all the manufacturer identifiers for the first element of goids
  goids[[1]]
  # Evidence code for the mappings
  names(goids[[1]])
}

```

illuminaHumanv2MAP *Map between Manufacturer Identifiers and cytogenetic maps/bands*

Description

illuminaHumanv2MAP is an R object that provides mappings between manufacturer identifiers and cytoband locations.

Details

Each manufacturer identifier is mapped to a vector of cytoband locations. The vector length may be one or longer, if there are multiple reported chromosomal locations for a given gene. An NA is reported for any manufacturer identifiers that cannot be mapped to a cytoband at this time.

Cytogenetic bands for most higher organisms are labeled p1, p2, p3, q1, q2, q3 (p and q are the p and q arms), etc., counting from the centromere out toward the telomeres. At higher resolutions, sub-bands can be seen within the bands. The sub-bands are also numbered from the centromere out toward the telomere. Thus, a label of 7q31.2 indicates that the band is on chromosome 7, q arm, band 3, sub-band 1, and sub-sub-band 2.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov>

Examples

```

x <- illuminaHumanv2MAP
# Get the probe identifiers that are mapped to any cytoband
mapped_probes <- mappedkeys(x)
# Convert to a list

```

```
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the MAP for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2MAPCOUNTS

Number of mapped keys for the maps in package illuminaHumanv2.db

Description

illuminaHumanv2MAPCOUNTS provides the "map count" (i.e. the count of mapped keys) for each map in package illuminaHumanv2.db.

Details

This "map count" information is precalculated and stored in the package annotation DB. This allows some quality control and is used by the [checkMAPCOUNTS](#) function defined in AnnotationDbi to compare and validate different methods (like `count.mappedkeys(x)` or `sum(!is.na(as.list(x)))`) for getting the "map count" of a given map.

See Also

[mappedkeys](#), [count.mappedkeys](#), [checkMAPCOUNTS](#)

Examples

```
illuminaHumanv2MAPCOUNTS
mapnames <- names(illuminaHumanv2MAPCOUNTS)
illuminaHumanv2MAPCOUNTS[mapnames[1]]
x <- get(mapnames[1])
sum(!is.na(as.list(x)))
count.mappedkeys(x) # much faster!

## Check the "map count" of all the maps in package illuminaHumanv2.db
checkMAPCOUNTS("illuminaHumanv2.db")
```

illuminaHumanv2listNewMappings

Custom mappings added to the package

Description

We have used an extensive re-annotation of the illuminaHumanv2 probe sequences to provide additional information that is not captured in the standard Bioconductor packages. Whereas Bioconductor annotations are based on the RefSeq ID that each probe maps to, our additional mappings provide data specific to each probe on the platform. See below for details. We recommend using the probe quality as a form of filtering, and retaining only perfect or good probes for an analysis.

Details of custom mappings

- illuminaHumanv2listNewMappings** List all the custom re-annotation mappings provided by the package
- illuminaHumanv2fullReannotation** Return all the re-annotation information as a matrix
- illuminaHumanv2ARRAYADDRESS** Array Address code used to identify the probe at the bead-level
- illuminaHumanv2NUID** Lumi's nuID (universal naming scheme for oligonucleotides) Reference: Du et al. (2007), Biol Direct 2:16
- illuminaHumanv2PROBESEQUENCE** The 50 base sequence for the probe
- illuminaHumanv2PROBEQUALITY** Quality grade assigned to the probe: "Perfect" if it perfectly and uniquely matches the target transcript; "Good" if the probe, although imperfectly matching the target transcript, is still likely to provide considerably sensitive signal (up to two mismatches are allowed, based on empirical evidence that the signal intensity for 50-mer probes with less than 95% identity to the respective targets is less than 50% of the signal associated with perfect matches *); "Bad" if the probe matches repeat sequences, intergenic or intronic regions, or is unlikely to provide specific signal for any transcript; "No match" if it does not match any genomic region or transcript.
- illuminaHumanv2CODINGZONE** Coding status of target sequence: intergenic / intronic / Transcriptomic ("Transcriptomic" when the target transcript is non-coding or there is no information on the coding sequence)
- illuminaHumanv2GENOMICLOCATION** Probe's genomic coordinates (hg19 for human, mm9 for mouse or rn4 for rat)
- illuminaHumanv2GENOMICMATCHSIMILARITY** Percentage of similarity between the probe and its best genomic match in the alignable region, taking the probe as reference
- illuminaHumanv2SECONDMATCHES** Genomic coordinates of second best matches between the probe and the genome
- illuminaHumanv2SECONDMATCHSIMILARITY** Percentage of similarity between the probe and its second best genomic match in the alignable region, taking the probe as reference
- illuminaHumanv2TRANSCRIPTOMICMATCHSIMILARITY** Percentage of similarity between the probe and its target transcript in the alignable region, taking the probe as reference
- illuminaHumanv2OTHERGENOMICMATCHES** Genomic coordinates of sequences as alignable with the probe (in terms of number of matching nucleotides) as its main target
- illuminaHumanv2REPEATMASK** Overlapping RepeatMasked sequences, with number of bases overlapped by the repeat
- illuminaHumanv2OVERLAPPINGSNP** Overlapping annotated SNPs
- illuminaHumanv2ENTREZREANNOTATED** Entrez IDs
- illuminaHumanv2ENSEMBLREANNOTATED** Ensembl IDs
- illuminaHumanv2SYMBOLREANNOTATED** Gene symbol derived by re-annotation
- illuminaHumanv2REPORTERGROUPID** For probes marked as controls in Illuminas annotation file, these gives the type of control
- illuminaHumanv2REPORTERGROUPNAME** Usually a more informative name for the control type

References

<http://remoat.sysbiol.cam.ac.uk>

Barbosa-Morais et al. (2010) A re-annotation pipeline for Illumina BeadArrays: improving the interpretation of gene expression data. Nucleic Acids Research

Examples

```
##See what new mappings are available

illuminaHumanv2listNewMappings()

x <- illuminaHumanv2PROBEQUALITY

mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the PROBEQUALITY for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

##Overall table of qualities
table(unlist(xx))

x <- illuminaHumanv2ARRAYADDRESS

mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the ARRAYADDRESS for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

##Can do the mapping from array address to illumina ID using a revmap

y<- revmap(illuminaHumanv2ARRAYADDRESS)

mapped_probes <- mappedkeys(y)
# Convert to a list
yy <- as.list(y[mapped_probes])
if(length(yy) > 0) {
  # Get the ARRAYADDRESS for the first five probes
  yy[1:5]
  # Get the first one
  yy[[1]]
}

x <- illuminaHumanv2CODINGZONE

mapped_probes <- mappedkeys(x)
```

```

# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the CODINGZONE for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

x <- illuminaHumanv2PROBESEQUENCE

mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the PROBESEQUENCE for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

```

illuminaHumanv2OMIM	<i>Map between Manufacturer Identifiers and Mendelian Inheritance in Man (MIM) identifiers</i>
---------------------	--

Description

illuminaHumanv2OMIM is an R object that provides mappings between manufacturer identifiers and OMIM identifiers.

Details

Each manufacturer identifier is mapped to a vector of OMIM identifiers. The vector length may be one or longer, depending on how many OMIM identifiers the manufacturer identifier maps to. An NA is reported for any manufacturer identifier that cannot be mapped to an OMIM identifier at this time.

OMIM is based upon the book Mendelian Inheritance in Man (V. A. McKusick) and focuses primarily on inherited or heritable genetic diseases. It contains textual information, pictures, and reference information that can be searched using various terms, among which the MIM number is one.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene> <http://www3.ncbi.nlm.nih.gov/entrez/query.fcgi?db=OMIM>

Examples

```
x <- illuminaHumanv2OMIM
# Get the probe identifiers that are mapped to a OMIM ID
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the OMIM for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2ORGANISM

The Organism information for illuminaHumanv2

Description

illuminaHumanv2ORGANISM is an R object that contains a single item: a character string that names the organism for which illuminaHumanv2 was built. illuminaHumanv2ORGPKG is an R object that contains a character vector with the name of the organism package that a chip package depends on for its gene-centric annotation.

Details

Although the package name is suggestive of the organism for which it was built, illuminaHumanv2ORGANISM provides a simple way to programmatically extract the organism name. illuminaHumanv2ORGPKG provides a simple way to programmatically extract the name of the parent organism package. The parent organism package is a strict dependency for chip packages as this is where the gene centric information is ultimately extracted from. The full package name will always be this string plus the extension ".db". But most programatic acces will not require this extension, so its more convenient to leave it out.

Examples

```
illuminaHumanv2ORGANISM
illuminaHumanv2ORGPKG
```

illuminaHumanv2PATH

Mappings between probe identifiers and KEGG pathway identifiers

Description

KEGG (Kyoto Encyclopedia of Genes and Genomes) maintains pathway data for various organisms.

illuminaHumanv2PATH maps probe identifiers to the identifiers used by KEGG for pathways in which the genes represented by the probe identifiers are involved

illuminaHumanv2PATH2PROBE is an R object that provides mappings between KEGG identifiers and manufacturer identifiers.

Details

Each KEGG pathway has a name and identifier. Pathway name for a given pathway identifier can be obtained using the KEGG data package that can either be built using AnnBuilder or downloaded from Bioconductor <http://www.bioconductor.org>.

Graphic presentations of pathways are searchable at url <http://www.genome.ad.jp/kegg/pathway.html> by using pathway identifiers as keys.

Mappings were based on data provided by: KEGG GENOME <ftp://ftp.genome.jp/pub/kegg/genomes> With a date stamp from the source of: 2011-Mar15

References

<http://www.genome.ad.jp/kegg/>

Examples

```
x <- illuminaHumanv2PATH
# Get the probe identifiers that are mapped to a KEGG pathway ID
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the PATH for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}

# Now convert the illuminaHumanv2PATH2PROBE object to a list
xx <- as.list(illuminaHumanv2PATH2PROBE)
if(length(xx) > 0){
  # Get the probe identifiers for the first two pathway identifiers
  xx[1:2]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2PMID *Maps between Manufacturer Identifiers and PubMed Identifiers*

Description

illuminaHumanv2PMID is an R object that provides mappings between manufacturer identifiers and PubMed identifiers. illuminaHumanv2PMID2PROBE is an R object that provides mappings between PubMed identifiers and manufacturer identifiers.

Details

When illuminaHumanv2PMID is viewed as a list each manufacturer identifier is mapped to a named vector of PubMed identifiers. The name associated with each vector corresponds to the manufacturer identifier. The length of the vector may be one or greater, depending on how many PubMed identifiers a given manufacturer identifier is mapped to. An NA is reported for any manufacturer identifier that cannot be mapped to a PubMed identifier.

When `illuminaHumanv2PMID2PROBE` is viewed as a list each PubMed identifier is mapped to a named vector of manufacturer identifiers. The name represents the PubMed identifier and the vector contains all manufacturer identifiers that are represented by that PubMed identifier. The length of the vector may be one or longer, depending on how many manufacturer identifiers are mapped to a given PubMed identifier.

Titles, abstracts, and possibly full texts of articles can be obtained from PubMed by providing a valid PubMed identifier. The `pubmed` function of `annotate` can also be used for the same purpose.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=PubMed>

Examples

```
x <- illuminaHumanv2PMID
# Get the probe identifiers that are mapped to any PubMed ID
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0){
  # Get the PubMed identifiers for the first two probe identifiers
  xx[1:2]
  # Get the first one
  xx[[1]]
  if(interactive() && !is.null(xx[[1]]) && !is.na(xx[[1]]))
    && require(annotate){
      # Get article information as XML files
      xmls <- pubmed(xx[[1]], disp = "data")
      # View article information using a browser
      pubmed(xx[[1]], disp = "browser")
    }
}

# Now convert the reverse map object illuminaHumanv2PMID2PROBE to a list
xx <- as.list(illuminaHumanv2PMID2PROBE)
if(length(xx) > 0){
  # Get the probe identifiers for the first two PubMed identifiers
  xx[1:2]
  # Get the first one
  xx[[1]]
  if(interactive() && require(annotate)){
    # Get article information as XML files for a PubMed id
    xmls <- pubmed(names(xx)[1], disp = "data")
    # View article information using a browser
    pubmed(names(xx)[1], disp = "browser")
  }
}
```

illuminaHumanv2SYMBOL *Map between Manufacturer Identifiers and Gene Symbols*

Description

illuminaHumanv2SYMBOL is an R object that provides mappings between manufacturer identifiers and gene abbreviations.

Details

Each manufacturer identifier is mapped to an abbreviation for the corresponding gene. An NA is reported if there is no known abbreviation for a given gene.

Symbols typically consist of 3 letters that define either a single gene (ABC) or multiple genes (ABC1, ABC2, ABC3). Gene symbols can be used as key words to query public databases such as Entrez Gene.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene>

Examples

```
x <- illuminaHumanv2SYMBOL
# Get the probe identifiers that are mapped to a gene symbol
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the SYMBOL for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2UNIGENE

Map between Manufacturer Identifiers and UniGene cluster identifiers

Description

illuminaHumanv2UNIGENE is an R object that provides mappings between manufacturer identifiers and UniGene identifiers.

Details

Each manufacturer identifier is mapped to a UniGene identifier. An NA is reported if the manufacturer identifier cannot be mapped to UniGene at this time.

A UniGene identifier represents a cluster of sequences of a gene. Using UniGene identifiers one can query the UniGene database for information about the sequences or the Entrez Gene database for information about the genes.

Mappings were based on data provided by: Entrez Gene <ftp://ftp.ncbi.nlm.nih.gov/gene/DATA> With a date stamp from the source of: 2015-Mar17

References

<http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?db=gene>

Examples

```
x <- illuminaHumanv2UNIGENE
# Get the probe identifiers that are mapped to an UNIGENE ID
mapped_probes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_probes])
if(length(xx) > 0) {
  # Get the UNIGENE for the first five probes
  xx[1:5]
  # Get the first one
  xx[[1]]
}
```

illuminaHumanv2UNIPROT

Map Uniprot accession numbers with Entrez Gene identifiers

Description

illuminaHumanv2UNIPROT is an R object that contains mappings between the manufacturer identifiers and Uniprot accession numbers.

Details

This object is a simple mapping of manufacturer identifiers to Uniprot Accessions.

Mappings were based on data provided by NCBI (link above) with an exception for fly, which required retrieving the data from ensembl <http://www.ensembl.org/biomart/martview/>

Examples

```
x <- illuminaHumanv2UNIPROT
# Get the entrez gene IDs that are mapped to an Uniprot ID
mapped_genes <- mappedkeys(x)
# Convert to a list
xx <- as.list(x[mapped_genes])
if(length(xx) > 0) {
  # Get the Uniprot IDs for the first five genes
  xx[1:5]
```

```
# Get the first one
xx[[1]]
}
```

illuminaHumanv2_dbconn

Collect information about the package annotation DB

Description

Some convenience functions for getting a connection object to (or collecting information about) the package annotation DB.

Usage

```
illuminaHumanv2_dbconn()
illuminaHumanv2_dbfile()
illuminaHumanv2_dbschema(file="", show.indices=FALSE)
illuminaHumanv2_dbInfo()
```

Arguments

file	A connection, or a character string naming the file to print to (see the file argument of the <code>cat</code> function for the details).
show.indices	The CREATE INDEX statements are not shown by default. Use show.indices=TRUE to get them.

Details

`illuminaHumanv2_dbconn` returns a connection object to the package annotation DB. **IMPORTANT:** Don't call `dbDisconnect` on the connection object returned by `illuminaHumanv2_dbconn` or you will break all the `AnnDbObj` objects defined in this package!

`illuminaHumanv2_dbfile` returns the path (character string) to the package annotation DB (this is an SQLite file).

`illuminaHumanv2_dbschema` prints the schema definition of the package annotation DB.

`illuminaHumanv2_dbInfo` prints other information about the package annotation DB.

Value

`illuminaHumanv2_dbconn`: a `DBIConnection` object representing an open connection to the package annotation DB.

`illuminaHumanv2_dbfile`: a character string with the path to the package annotation DB.

`illuminaHumanv2_dbschema`: none (invisible NULL).

`illuminaHumanv2_dbInfo`: none (invisible NULL).

See Also

[dbGetQuery](#), [dbConnect](#), [dbconn](#), [dbfile](#), [dbschema](#), [dbInfo](#)

Examples

```
## Count the number of rows in the "probes" table:  
dbGetQuery(illuminaHumanv2_dbconn(), "SELECT COUNT(*) FROM probes")  
  
illuminaHumanv2_dbschema()  
  
illuminaHumanv2_dbInfo()
```

Index

* datasets

- [illuminaHumanv2.db](#), [2](#)
- [illuminaHumanv2_dbconn](#), [21](#)
- [illuminaHumanv2ACCNUM](#), [1](#)
- [illuminaHumanv2ALIAS2PROBE](#), [2](#)
- [illuminaHumanv2CHR](#), [3](#)
- [illuminaHumanv2CHRENGTHS](#), [3](#)
- [illuminaHumanv2CHRLOC](#), [4](#)
- [illuminaHumanv2ENSEMBL](#), [4](#)
- [illuminaHumanv2ENTREZID](#), [5](#)
- [illuminaHumanv2ENZYME](#), [6](#)
- [illuminaHumanv2GENENAME](#), [7](#)
- [illuminaHumanv2GO](#), [8](#)
- [illuminaHumanv2listNewMappings](#), [11](#)
- [illuminaHumanv2MAP](#), [10](#)
- [illuminaHumanv2MAPCOUNTS](#), [11](#)
- [illuminaHumanv2OMIM](#), [14](#)
- [illuminaHumanv2ORGANISM](#), [15](#)
- [illuminaHumanv2PATH](#), [15](#)
- [illuminaHumanv2PMID](#), [16](#)
- [illuminaHumanv2REFSEQ](#), [18](#)
- [illuminaHumanv2SYMBOL](#), [19](#)
- [illuminaHumanv2UNIGENE](#), [19](#)
- [illuminaHumanv2UNIPROT](#), [20](#)

* utilities

- [illuminaHumanv2_dbconn](#), [21](#)

[AnnDbObj](#), [21](#)

[cat](#), [21](#)

[checkMAPCOUNTS](#), [11](#)

[count.mappedkeys](#), [11](#)

[dbconn](#), [21](#)

[dbConnect](#), [21](#)

[dbDisconnect](#), [21](#)

[dbfile](#), [21](#)

[dbGetQuery](#), [21](#)

[dbInfo](#), [21](#)

[dbschema](#), [21](#)

[illuminaHumanv2\(illuminaHumanv2.db\)](#), [2](#)

[illuminaHumanv2.db](#), [2](#)

[illuminaHumanv2_dbconn](#), [21](#)

[illuminaHumanv2_dbfile](#)

([illuminaHumanv2_dbconn](#)), [21](#)

[illuminaHumanv2_dbInfo](#)

([illuminaHumanv2_dbconn](#)), [21](#)

[illuminaHumanv2_dbschema](#)

([illuminaHumanv2_dbconn](#)), [21](#)

[illuminaHumanv2ACCNUM](#), [1](#)

[illuminaHumanv2ALIAS2PROBE](#), [2](#)

[illuminaHumanv2ARRAYADDRESS](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2CHR](#), [3](#)

[illuminaHumanv2CHRENGTHS](#), [3](#)

[illuminaHumanv2CHRLOC](#), [4](#)

[illuminaHumanv2CHRLOCEND](#)

([illuminaHumanv2CHRLOC](#)), [4](#)

[illuminaHumanv2CODINGZONE](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2ENSEMBL](#), [4](#)

[illuminaHumanv2ENSEMBL2PROBE](#)

([illuminaHumanv2ENSEMBL](#)), [4](#)

[illuminaHumanv2ENSEMBLREANNOTATED](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2ENTREZID](#), [5](#)

[illuminaHumanv2ENTREZREANNOTATED](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2ENZYME](#), [6](#)

[illuminaHumanv2ENZYME2PROBE](#)

([illuminaHumanv2ENZYME](#)), [6](#)

[illuminaHumanv2fullReannotation](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2GENENAME](#), [7](#)

[illuminaHumanv2GENOMICLOCATION](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2GENOMICMATCHSIMILARITY](#)

([illuminaHumanv2listNewMappings](#)),

[11](#)

[illuminaHumanv2GO](#), [8](#)

- illuminaHumanv2G02ALLPROBES, [9](#)
- illuminaHumanv2G02ALLPROBES
(illuminaHumanv2GO), [8](#)
- illuminaHumanv2G02PROBE
(illuminaHumanv2GO), [8](#)
- illuminaHumanv2listNewMappings, [11](#)
- illuminaHumanv2LOCUSID
(illuminaHumanv2ENTREZID), [5](#)
- illuminaHumanv2MAP, [10](#)
- illuminaHumanv2MAPCOUNTS, [11](#)
- illuminaHumanv2NUID
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2OMIM, [14](#)
- illuminaHumanv2ORGANISM, [15](#)
- illuminaHumanv2ORGPKG
(illuminaHumanv2ORGANISM), [15](#)
- illuminaHumanv2OTHERGENOMICMATCHES
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2OVERLAPPINGSNP
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2PATH, [15](#)
- illuminaHumanv2PATH2PROBE
(illuminaHumanv2PATH), [15](#)
- illuminaHumanv2PMID, [16](#)
- illuminaHumanv2PMID2PROBE
(illuminaHumanv2PMID), [16](#)
- illuminaHumanv2PROBEQUALITY
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2PROBESEQUENCE
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2REFSEQ, [18](#)
- illuminaHumanv2REPEATMASK
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2REPORTERGROUPID
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2REPORTERGROUPNAME
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2SECONDMATCHES
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2SECONDMATCHSIMILARITY
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2SYMBOL, [19](#)
- illuminaHumanv2SYMBOLREANNOTATED
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2TRANSCRIPTOMICMATCHSIMILARITY
(illuminaHumanv2listNewMappings),
[11](#)
- illuminaHumanv2UNIGENE, [19](#)
- illuminaHumanv2UNIPROT, [20](#)
- illuminaHumanv2UNIPROT2PROBE
(illuminaHumanv2UNIPROT), [20](#)
- mappedkeys, [11](#)